Claims

- [c1] A welding apparatus for a welding process in a straight polarity configuration comprising:

 a welding gun having means for feeding an electrode into the welding gun; the electrode comprising a sheath encapsulating a core having a core composition, the core composition comprising a combination of graphite and one or more compounds of potassium, the combination of graphite and compounds of potassium in the core composition not exceeding approximately 5% by weight; and a power source supplying electrical current to the electrode.
 - 2. The welding apparatus of Claim 1, further comprising a gas source supplying a shielding gas to the welding apparatus.
- [c3] 3.The welding apparatus of Claim 1, wherein the welding process is gas metal arc welding.
- [c4] 4. The welding apparatus of Claim 1, wherein the means for feeding the electrode into the welding gun comprise a wire drive and a wire reel.
- [c5] 5. The welding apparatus of Claim 1, wherein one or more compounds of potassium comprise K $_2$ MnTiO $_4$ and K $_2$ SO $_4$.
- [c6] 6.The welding apparatus of Claim 5, wherein the combination is selected from the range from about 0.3% to about 5.0%.
- [c7] 7. The welding apparatus of Claim 2, wherein the shielding gas comprises a mixture of Ar and CO $_{\rm 2}$.
- [c8] 8.A wire comprising a sheath encapsulating a core having a core composition, the core composition comprising a combination of graphite and one or more compounds of potassium, the combination of graphite and compounds of potassium in the core composition not exceeding approximately 5% by weight.
- [c9] 9.The wire of Claim 8, wherein the compounds of potassium comprise K $_{2}$ MnTiO $_{4}$ and K $_{2}$ SO $_{4}$.

ı dğ

[c2]

- [c10] 10.The wire of Claim 8, wherein the combination of graphite and one or more compounds of potassium in the core composition is selected from the range of about 0.3% to about 5% by weight.
- [c11] 11.The wire of Claim 10, wherein the compounds of potassium comprise K $_{\rm 2}$ MnTiO $_{\rm 4}$ and K $_{\rm 2}$ SO $_{\rm 4}$.
- [c12] 12.A process of manufacturing a metal-cored wire comprising:
 shaping a metal sheath into a fillable shape;
 filling the sheath with a core composition to form a core, the core composition comprising a combination of graphite and one or more compounds of potassium, the combination not exceeding approximately 5% by weight; and encapsulating the core by the sheath to form a metal-cored wire.
- [c13] 13.The process of Claim 12, wherein the compounds of potassium comprise K $_2$ MnTiO $_4$ and K $_2$ SO $_4$.
- [c14] 14. The process of Claim 12, wherein the core composition is a powder.
- [c15] 15.The process of Claim 12, wherein the combination is selected from a range of about 0.3% to about 5.0% by weight.
- [c16] 16.The process of Claim 15, wherein the compounds of potassium comprise K MnTiO $_4$ and K $_2$ SO $_4$.
- [c17]
 17. A welding process in a straight polarity configuration comprising:
 providing a welding apparatus having means for feeding an electrode into the
 welding apparatus and means for supplying a shielding gas into the welding
 apparatus;

coupling the welding apparatus to a power source in the straight polarity configuration and forming an arc;

feeding the electrode into the welding apparatus, the electrode comprising a sheath and a core having a core composition, the core composition comprising a combination of graphite and one or more compounds of potassium, the combination of graphite and compounds of potassium in the core composition not exceeding approximately 5% by weight; and

[c23]

and the arc.
18. The welding process of Claim 17, wherein supplying the shielding gas into the welding apparatus comprises providing an external gas source.
19. The welding process of Claim 17, wherein feeding the electrode into the welding apparatus comprises providing means for feeding the electrode that is external to the welding apparatus.
20.The welding process of Claim 17, wherein supplying the shielding gas comprises providing a mixture of Ar and CO $_{\rm 2}$.
21. The welding process of Claim 17, wherein the welding process is a gas metal arc welding process.
22. The welding process of Claim 17, wherein one or more compounds of potassium comprise K $_2$ MnTiO $_4$ and K $_2$ SO $_4$.

23. The welding process of Claim 22, wherein the combination is selected from

the range from about 0.3% to about 5.0%.

supplying the shielding gas into the welding apparatus to shield the electrode